

MULCHER KTS - FU(N)MX

Schlegeltypen



Rotordurchmesser 205mm
ZW 540 oder 1000 U/min.



TYP	Arbeitsbreite mm	Gesamtbreite mm	Kraftbedarf PS	Anzahl		Gewicht kg
				Messer ZS-NS-DZ/Z	Schlegel LS	
KTS-FU(N)MX 150	1500	1650	40 – 50	12/42	30	610
KTS-FU(N)MX 162	1625	1775	50 – 60	13/42	30	660
KTS-FU(N)MX 175	1750	1900	60 – 70	14/48	36	714
KTS-FU(N)MX 200	2000	2150	70 – 80	16/54	42	816
KTS-FU(N)MX 225	2250	2400	80 – 90	18/60	48	918
KTS-FU(N)MX 250	2500	2650	90 – 100	20/66	54	1020
KTS-FU(N)MX 280	2800	2950	100 – 110	22/72	60	1140
KTS-FU(N)MX 300	3000	3150	110 – 120	24/78	66	1220

Extras:

hydraulische Seitenverschiebung

Front – Heck Anbau und Getriebe mit Durchtrieb

ACKER

KONSTANTINIDIS & Co. AG
GR 57 022 SINDOS – THESSALONIKI
Tel: (0030)2310 – 797.984, 797.985
Fax : (0030) 2310 – 799.627

www.acker.gr
e-mail: info@acker.gr
GRIECHENLAND

TÜV HELLAS

